



**Argyle | materials inc.**

Argyle Materials PCABS-FR DATASHEET

January 7, 2016

Tensile Strength	8560 PSI	ASTM D638
Notched Izod Impact 0.125"	10.0 ft-lbs/in	ASTM D256
Flex Modulus	348,000 PSI	ASTM D790
Flex Strength	12,900 PSI	ASTM D790
Heat deflection @ 264 psi	227 F	ASTM D648
Flame Rating	V0	UL 94

Note: The information provided on this datasheet should only be used as a guideline. Actual lot to lot values will vary.

Disclaimer: No information supplied by Argyle Materials, Inc. constitutes a warranty regarding product performance or use. Any information regarding performance or use is only offered as suggestion for investigation for use, based upon Argyle Materials, Inc. or other customer experience. Argyle Materials, Inc. makes no warranties, expressed or implied, concerning the suitability or fitness of any of its products for any particular purpose. It is the responsibility of the customer to determine that the product is safe, lawful and technically suitable for the intended use. The disclosure of information herein is not a license to operate under, or a recommendation to infringe any patents.



Argyle Materials, Inc., 141 Reach Street, Unit 9, Uxbridge, ON L9P 1L3,  
T: 905-852-1004, F: 905-852-1546 [sales@argylematerials.com](mailto:sales@argylematerials.com) [www.argylematerials.com](http://www.argylematerials.com)